

Residential Unit mod. Flow Mini



Deep Hygiene



Silent



Safe



Eco Friendly



Practical



Versatile

Residential unit mod. Flow Mini.

Number of Users: 1

Work area: Up to 120m²

Socket points with iFlex line: Up to 2 with a 12m hose.

Socket points with traditional line: Up to 4 with a 7m hose.

Installation in embedded box: Yes.

Installation in outdoor box: Yes.

Contact System: For wired system activation and shutdown. The unit starts when an electrical contact is established at the vacuum inlet.

Noise reduction: Integrated silencer, patented system for noise suppression of the air expelled from the unit.

Dust container release: Patented system for easy hooking and unhooking of the container with handle and front button. Also allows installation adjacent to walls.

Filter release: Quick-release system via a filter locking ring.



Residential unit mod. Flow Mini.

Number of Users: 1

Work area: Up to 120m²

Double motor protection system: Automatic shutdown of the unit in case of clogged through an "Adaptive Sensing" device; thermal sensor in the electrical motor.

Motor: Mono-stage Through-Flow motor

Soft Start: "Soft start" system of the motor to eliminate the power surge during startup.

Self-locking system: Frontal fixing on a dedicated wall bracket, and release by pressing two lateral tabs. This unique features allows installation even in restricted spaces.

Reversible aspiration and exhaust: The inlet and outlet can be positioned on the right or left side of the unit, or crossed, depending on customer needs.

Installation: Suitable for both indoor and outdoor installation, protected from direct rain. Manufactured from high-quality ABS, they don't suffer the oxidation process common to all metallic products.

General D'Aspirazione

Since 1974 pioneers in the Italian market
in centralized vacuum cleaning sector.



Residential unit mod. Flow Mini.

Number of Users: 1

Work area: Up to 120m²

Internal Filter Protection: Filter protection device against direct impact from solid particles, also facilitating the cyclonic motion of the vacuum unit.

Included in the Package:

- 1 Wall bracket with 4 plugs and screws
- 2 Flexible hose to join the pipes to the unit
- 4 Metal hose clamps
- 1 Spare bag



Technical Information.

Technical data		Flow Mini
Number of Users		1
Work Area	m ²	0-120
Max. number of iFlex sockets	n	2
Max. number of traditional sockets	n	4
Farthest outlet distance	m	30
Integrated wireless		NO
Integrated silencer		YES
Touch interface + App		NO
Dimensions		
Dust container capacity	l	8
Diameter	cm	30
Filtering surface	m ²	0,4
Ø Inlet/outlet	mm	50
Height	cm	60
Width	cm	37
Weight	kg	9
Technical performance data at 230V		
Maximum airflow	m ³ /h	187
Depression	mmH ₂ O	2.890
Maximum noise level*	dB A	61
Aspiration power	Airwatt	566
Electrical technical data		
Motor power	W	1250
Power supply	V	220-240
Power supply frequency	Hz	50-60
Current draw	A	5,9
Motor thermal protection		YES
Auto shut-off protection	SENSING	NO
Delayed fuse	A	8
Sockets supply	Vdc	5
Electrical insulation	Class II	<input type="checkbox"/>


* Noise level measured according to UNI EN ISO 3744 standard

General D'Aspirazione

Since 1974 pioneers in the Italian market
in centralized vacuum cleaning sector.




Installation measures.



General D'Aspirazione

Since 1974 pioneers in the Italian market in centralized vacuum cleaning sector.






General D'Aspirazione
Since 1974 pioneers in the Italian market
in centralized vacuum cleaning sector.

Support.

If you need help, contact your dealer who will provide you with the correct assistance.



OLK/



General D'Aspirazione s.a.s.

generaldaspirazione.com
+ 39 0541 931012

Del Lavoro street, 9/11 - San Mauro Pascoli - 47030 (FC) Italy