

Industrial System



Year 2025

Technical Sheet
generaldaspirazione.com





Deep Hygiene



Silent



Safe



Eco Friendly



Practical



Versatile

Industrial System.

Ideals for external plants installations in production areas

Pipes and fittings in galvanized steel or, where required, in AISI 304 Stainless Steel, for external installations or where electrical conductivity is necessary.

When specific, abrasive, or electrostatic materials must be removed after the production process, the ideal solution is to use this kind of system.

Suitable for ATEX Environments: This kind of galvanized piping and fittings can be installed in ATEX-rated environments, thanks to their electrical conductivity which allows grounding to the plant's earthing system, ensuring maximum safety levels.

Easy Installation: Quick assembly using leak-proof coupling without the need for glues or sealants.

Available Diameters: Pipes and fittings are available in 50, 63, 76, and 102mm diameters. Plant dimensioning will be designed according to the customer's specific requirements.

Industrial System.

Ideals for external plants installations in production areas



Galvanized Steel
Pipe 50-63-76-102mm



Galvanized Steel
90° Elbow 50-63-76-102mm



Galvanized Steel
45° Elbow 50-63-76-102mm



Galvanized Steel
45° Wye 50-63-76-102mm

Industrial System.

Ideals for external plants installations in production areas

The installation is completed with external industrial sockets.
Working hoses and cleaning accessories are available in Ø 32, Ø 38, and Ø 50
diameters, in both conductive and antistatic versions.



Galvanized Steel
coupling 50-63-76-102mm



Galvanized Steel
Cap 50-63-76-102mm



Galvanized Steel
Increase 50-63-76-102mm



Industrial System.

Ideals for external plants installations in production areas

Industrial socket – Standard and antistatic series

- Made of PA6 + 30% fiberglass for direct installation on Ø50 or Ø63 pipe.
- Available with or without microswitch for system activation.
- Accessory connection available in Ø32, Ø38, or Ø50.
- Also available in antistatic version.
- Dimensions: 138 × 81mm



Standard
Industrial
socket

OLK/



General D'Aspirazione s.a.s.

generaldaspirazione.com
+ 39 0541 931012

Del Lavoro Street, 9/11 - San Mauro Pascoli - 47030 (FC) Italy